

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS									
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED					
2		AS DRAWN BY CANAM.	8/31/2012	JAG						
3	16-0104	UPDATED TO NEW STANDARD. CH'D DIM WAS .200 +.000003 IS .180, ADDED DIM (5/16-24 UNF-2A).	8/11/2016	DEW	SM					





DWG NO.

BUTTON HEAD SCREW SWA-3A SWIVEL

SWA3-400 MAT'L S.S. UNLESS OTHERWISE SPECIFIED SURFACES = 125 SPEC A T.I.

1. BREAK ALL SHARP EDGES

.015 x 45° OR .015R

2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009 DRAWN BY: CANAM CHECKED: DUERFELDT OPPS APPR: ANDERSON QA APPR: LINDSAY USED ON MODEL

ASSY QTY	ASSY QTY	В/О	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PC
			SWA3-400	1	BUTTON HEAD SCREW	S.S.	5/16-24 X 3/8 MCMASTER-CARR #92949A595 (MODIFIED)	1

APPROVED: MACKOVJAK SCALE 4:1 7/16/1997 SHEET 1 OF 1